

FELCO 22 - Green

Two-hand pruning shear - Lopper - Length 84 cm (33.1 in.) Made in Switzerland by FELCO







> Reliable: sturdy handles made of forged aluminium with a lifetime guarantee* / blade and screw-mounted anvil blade made of highquality hardened steel / clean, precise cut / all parts can be replaced

> Efficient: easy, durable cutting adjustment / wide blade opening

> Ergonomic: shock absorbers protect wrists and arms / handles with non-slip plastic coating

Our recommendation (* = Recommended, * * = Strongly recommended, * * * * = Best fit)Viticulture* * * *Arboriculture* * * *Parks and Gardens* * * *Small hand* * * *Average-sized hand* * * *Large hand* * * *Left-handed* * * *

RECOMMENDED FOR



THE POINTS OF EXCELLENCE



Straight cutting head

Ultra-precise cutting heads for the most demanding work.



Micrometric adjustment

FELCO's micrometric adjustment system guarantees an optimal adjustment of the cutting head throughout the life of the tool. It ensures a clean and precise cut.



Shock absorption system

The shock absorbers soften the impact upon finishing cutting as well as protecting the hand and wrist.

ACCESSORIES



FELCO 902 Sharpening tool Sharpening stone FELCO 903 Sharpening tool Sharpener




FELCO 980 Maintenance product Spray



FELCO 990 Maintenance product Grease



SPARE PARTS



FELCO	REF.	Designation	Composition	UCC Barcode
120	2/30	Adjustment key	1x 2/30	7 83929 40163 8
C°.	22/3	Blade	1x 22/3	7 83929 40041 9
(····)	22/4	Anvil-blade	1x 22/4	7 83929 40042 6
	21/93	Kit	2x 21/10	7 83929 40059 4
© =	20/94	Kit	1x 20/9 + 1x20/8	7 83929 40058 7
	22/1	Handle with coating, pin and shock absorber	1x 22/1 + 1x 20/2 + 1x 21/10 + 1x 22/5	7 83929 40184 3
	20/2	Coating	1x 20/2	7 83929 40173 7
	22/5	Pin	1x 22/5	7 83929 40185 0
	22/6	Hexagon screw	1x 22/6	7 83929 40186 7



==)	20/8	Bolt	1x 20/8	7 83929 40177 5
0	20/9	Nut	1x 20/9	7 83929 40178 2
Ø	C12/11	Counter nut	1x C12/11	7 83929 40317 5
XD	2/16	Locking segment	1x 2/16	7 83929 40157 7
ţm.	20/11	Screw for locking segment	1x 20/11	7 83929 40172 0
	21/10	Shock absorber	1x 21/10	7 83929 40183 6



MAINTENANCE





It is advisable to clean your tool after each use.

If your tool is particularly dirty or subject to rusting after exposure to moisture, do not delay cleaning.



Oiling

After cleaning, it is advisable to oil the tool so as to protect it from corrosion. The oil will also unjam the tool.



Sharpening

It is advisable to sharpen your tool at least once a day, but if you feel that your tool is not cutting as well as usual, sharpen it right away!



Dismantling

It is advisable to dismantle your tool on a regular basis, but at the very latest when it appears to be jammed.



PARTS REPLACEMENT



Changing the blade

When the blade and the anvil-blade no longer cross, or when the blade is badly damaged, it is advisable to change it.

Regulate the working of the blade and anvil-blade by adjusting the tightening of the nut. The blade should rub against the anvil-blade over 2/3 of its length.



Changing the anvil-blade

When the blade and anvil-blade no longer cross and the anvil-blade is badly damaged, it is advisable to change it.



Changing the shock absorbers

When the tool closes too abruptly during pruning the shock absorbers should be changed.