

The Gripple Lockable is for use in a dynamic or extreme load applications. Fundamentally a Gripple but with added security of locking screws engaging on the gripping mechanism.

ADVANTAGES

- Fast installation even on large diameters by means of the push-fit mechanism.
- Easy to work with large cumbersome cables.
- A range of products to suit wire rope/cables from diameter 5/64" to 3/8"
- Secondary locking mechanism for peace-of-mind.
- Available as a unit or ready-to-use anchor kits complete with cable.



INSTALLATION



- Using the pre-ferruled loop, hook the wire rope around the top of the anchor post.
- Slide the wire rope through one of the two Gripple channels (marked with an arrow).
- Pass the wire rope through the anchor point.
- Push the wire rope back into the second channel of the Gripple.
- Tension with the Gripple Torq Tensioning Tool (up to No.6 only)

SPECIFICATION

Product	Cable Range	Lockable on...
Lockable No.2	5/64" - 1/8"	Lockable on 5/64"
Lockable No.3	5/64" - 1/8"	Lockable on 1/8"
Lockable No.4	5/32" - 7/32"	Lockable on 5/32"
Lockable No.5	5/32" - 7/32"	Lockable on 3/16"
Lockable No.6	7/32" - 9/32"	Lockable on 1/4"
Lockable No.8 - NEW	5/16" - 3/8"	Lockable on 5/16"
Lockable No.10 - NEW	5/16" - 3/8"	Lockable on 3/8"