

FROST FREE YARD HYDRANT

**PROVIDES RUNNING WATER YEAR ROUND!
SUPPLY WATER TO REMOTE BUILDINGS AND PROPERTY
INSTALLS ANYWHERE USING PRESSURIZED WATER SUPPLY
USES INCLUDE: LAWN & GARDEN, LIVESTOCK, VEHICLE WASH-UP**

1 Optimum Flow Rates

- Superior design delivers optimum flow rates, surpassing other models

2 Heavy Duty Cast Iron Construction

- 3/4" garden hose connection
- Longer hand grip
- Locking eye



3 Lever Control/Adjustable Flow

- Thumb screw locks the handle in any position to regulate flow

4 Pivot Connector

- Features stainless steel set screw - allowing for easy adjustment without disassembly

5 Double O-Ring Sealing System

- Ensures positive seal between the hydrant and operating rod



*Hydrant elbow is recommended**

6 Stainless Steel Operating Rod

- Reduces wear on O-rings
- Excellent corrosion resistance

7 Stand Pipe

- 1" galvanized ASTM A53 schedule 40 pipe

8 Valve Body

- Double bypass design
- Self draining to prevent hydrant pipe and head from freezing

9 One-Piece Plunger

- Provides a positive seal

10 Convenient Repair:

NO DIGGING REQUIRED!
If required, maintenance and repairs to the hydrant can be done completely above ground.
All replacement parts available.

DETERMINING LENGTH REQUIRED:

The water source and hydrant base must be below the frost line.
(Check with your retailer)

This depth is known as the "bury".
i.e.: Our 4' bury hydrant has a 6' pipe which is buried 4' underground with approx.

22" clearance between ground level and the spout.

(Available in 1' to 6', 8' and 10' bury)

Tel: (519)-595-4444
Fax: (519)-595-4380

Toll Free: (800)-561-3164
Web: www.boshart.com

25 Whaley Ave., Milverton, Ontario, Canada N0K 1M0



Dedicated Sales Rep for Your Area



97% Fill Rate



Shipping within 24 Hours



State of the Art Warehouse System



Technical Support



Quality Control Program

